

View Online at <https://aerobasegroup.com/nsn/5962-01-048-9560>

**Body Length:**

Between 0.820 inches and 1.050 inches

**Body Width:**

Between 0.900 inches and 1.050 inches

**Body Height:**

Between 0.075 inches and 0.165 inches

**Maximum Power Dissipation Rating:**

3.0 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+125.0 degrees celsius

**Features Provided:**

Monolithic and hermetically sealed and positive outputs and medium speed and negative outputs

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Flat pack

**Input Circuit Pattern:**

16 input

**Design Function And Quantity:**

2 driver, high current

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

40.0 volts power source

**Time Rating Per Characteristic:**

210.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

22915-2-095 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

30 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0