## NSN 5962-01-048-9560

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-048-9560

View Online at https://aerobasegroup.com/nsn/5962-01-048-9560
Body Length:
Between 0.820 inches and 1.050 inches
Body Width:
Between 0.900 inches and 1.050 inches
Body Height:
Between 0.075 inches and 0.165 inches
Maximum Power Dissipation Rating:
3.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+125.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and positive outputs and medium speed and negative outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
16 input
Design Function And Quantity:
2 driver, high current
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
40.0 volts power source
Time Rating Per Chacteristic:
210.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low leve
output
Test Data Document:
22915-2-095 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
30 flat leads
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0