

View Online at <https://aerobasegroup.com/nsn/5962-01-048-9563>

**Body Length:**

Between 0.750 inches and 0.795 inches

**Body Width:**

Between 0.245 inches and 0.300 inches

**Body Height:**

Between 0.120 inches and 0.195 inches

**Maximum Power Dissipation Rating:**

46.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and edge triggered and low power and negative edge triggered and schottky and w/clear

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

Dual 3 input

**Design Function And Quantity:**

4 schmitt trigger and 4 multivibrator, monostable

**Case Outline Source And Designator:**

-0-001-ag joint electron device engineering council

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

5.5 volts power source

**Time Rating Per Characteristic:**

70.00 nanoseconds propagation delay time, low to high level output and 80.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0