## NSN 5962-01-049-1487

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-049-1487

**Body Length:** 

Between 0.240 inches and 0.275 inches

**Body Width:** 

Between 0.240 inches and 0.260 inches

**Body Height:** 

Between 0.030 inches and 0.070 inches

**Maximum Power Dissipation Rating:** 

750.0 milliwatts

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

**End Application:** 

Receiving set, radar type an/apr-38

**Features Provided:** 

Hermetically sealed and monolithic and negative outputs and positive outputs and w/enable

**Inclosure Material:** 

Ceramic and glass

**Inclosure Configuration:** 

Flat pack

**Input Circuit Pattern:** 

4 channel

**Design Function And Quantity:** 

4 switch, driver

**Case Outline Source And Designator:** 

T0-86 joint electron device engineering council

**Terminal Surface Treatment:** 

Solder

**Voltage Rating And Type Per Characteristic:** 

10.0 volts power source

**Time Rating Per Chacteristic:** 

300.00 nanoseconds propagation delay time, low to high level output and 750.00 nanoseconds propagation delay time, high to low level output

**Precious Material And Location:** 

Terminal surfaces gold

**Precious Material:** 

Gold

**Test Data Document:** 

03640-6088691 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:** 

14 flat leads

Shelf Life:

N/a

## NSN 5962-01-049-1487

Linear Microcircuit - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0