NSN 5962-01-049-2607

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-049-2607 **Body Length:** Between 1.180 inches and 1.220 inches **Body Width:** Between 0.560 inches and 0.600 inches **Body Height:** Between 0.100 inches and 0.140 inches **Maximum Power Dissipation Rating:** 2.0 watts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Test set, programmable, air data computer type an/asm-442 Monolithic and hermetically sealed and negative outputs and positive outputs and programmable and programmed and 3-state output and w/buffered output and w/decoded output **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** P-type metal oxide-semiconductor logic **Input Circuit Pattern:** 9 input **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -20.0 volts power source and 0.5 volts power source **Memory Device Type:** Rom **Memory Capacity:** Unknown **Test Data Document:** 97384-54494-40194 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 24 printed circuit Shelf Life: N/a

Demilitarization: Yes - demil/mli

Unit Of Measure:

NSN 5962-01-049-2607

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0