# NSN 5962-01-049-5246

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-049-5246

# **Body Length:**

Between 0.240 inches and 0.290 inches

# **Body Width:**

Between 0.240 inches and 0.260 inches

# **Body Height:**

Between 0.030 inches and 0.070 inches

# **Maximum Power Dissipation Rating:**

500.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **End Application:**

Receiving set radar, type an/apr-38

#### **Features Provided:**

Monolithic and hermetically sealed and negative outputs and positive outputs and high speed and w/gain select

#### **Inclosure Material:**

Ceramic and glass

# Inclosure Configuration:

Flat pack

#### Input Circuit Pattern:

2 stage

# Design Function And Quantity:

1 amplifier, differential and 1 amplifier, video

# Case Outline Source And Designator:

T0-91 joint electron device engineering council

# **Terminal Surface Treatment:**

Gold

# Voltage Rating And Type Per Characteristic:

6.0 volts power source

# **Time Rating Per Chacteristic:**

10.00 nanoseconds propagation delay time, low to high level output

#### **Precious Material And Location:**

Terminal surfaces gold

#### **Precious Material:**

Gold

#### Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Terminal Type And Quantity:

10 flat leads

# Shelf Life:

N/a

# NSN 5962-01-049-5246

Linear Microcircuit - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

