

View Online at <https://aerobasegroup.com/nsn/5962-01-050-6918>

Body Length:

Between 0.750 inches and 0.795 inches

Body Width:

Between 0.245 inches and 0.300 inches

Body Height:

Between 0.120 inches and 0.195 inches

Maximum Power Dissipation Rating:

657.0 milliwatts

Operating Temperature Range:

+0.0/+75.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and w/enable and high speed and programmable and programmed and w/open collector and schottky and bipolar and w/buffered output and w/decoded output and expandable and w/disable

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

10 input

Case Outline Source And Designator:

Mo-001-ag joint electron device engineering council

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Characteristic:

75.00 nanoseconds propagation delay time, low to high level output

Memory Device Type:

Prom

Memory Capacity:

Unknown

Test Data Document:

94117-7013655 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0