# NSN 5962-01-050-6945

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-050-6945

## **Body Length:**

Between 0.915 inches and 0.925 inches

### **Body Width:**

Between 0.245 inches and 0.252 inches

## **Body Height:**

Between 0.115 inches and 0.125 inches

# **Maximum Power Dissipation Rating:**

532.48 milliwatts

#### **Operating Tempurature Range:**

+0.0/+75.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Bipolar and 3-state output and monolithic and w/disable

#### Inclosure Material:

Plastic

## Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Transistor-transistor logic

# Input Circuit Pattern:

12 input

#### **Current Rating Per Characteristic:**

140.00 milliamperes supply

#### **Terminal Surface Treatment:**

Solder

# Voltage Rating And Type Per Characteristic:

7.0 volts power source

#### **Capitance Rating Per Characteristic:**

5.00 input picofarads and 8.00 output picofarads

#### Time Rating Per Chacteristic:

60.00 nanoseconds access

#### Memory Device Type:

Rom

# **Terminal Type And Quantity:**

18 printed circuit

#### Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

# NSN 5962-01-050-6945

Memory Microcircuit - Page 2 of 2

**Fiig:** A458a0

