## NSN 5962-01-050-8716

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-050-8716

| Body Outside Diameter:   |
|--|
| 0.600 inches   |
| Body Height:   |
| 0.200 inches   |
| Operating Tempurature Range:   |
| -10.0/+70.0 degrees celsius  |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| End Application:   |
| Terminal board type tb-16/bq   |
| Features Provided:   |
| Hermetically sealed and hybrid and negative outputs and positive outputs   |
| Inclosure Material:  |
| Glass and metal  |
| Inclosure Configuration:   |
| Can  |
| Input Circuit Pattern:   |
| 5 input  |
| Design Function And Quantity:  |
| 1 amplifier, preamplifier  |
| Terminal Surface Treatment:  |
| Gold   |
| Voltage Rating And Type Per Characteristic:  |
| 12.0 volts power source  |
| Precious Material And Location:  |
| Terminals gold   |
| Precious Material:   |
| Gold   |
| Test Data Document:  |
| 54497-0141a0452 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)                    |
| Terminal Type And Quantity:  |
| 16 pin   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| -  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A458a0   |