

View Online at <https://aerobasegroup.com/nsn/5962-01-051-3402>

**Body Length:**

0.840 inches

**Body Width:**

Between 0.220 inches and 0.310 inches

**Body Height:**

Between 0.140 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

50.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and w/enable and high speed and edge triggered and low power and schottky and synchronous and asynchronous and w/clear and presettable

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

Dual 5 input

**Design Function And Quantity:**

2 flip-flop, j-k, clocked

**Case Outline Source And Designator:**

D-2 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

5.5 volts power source

**Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

16 printed circuit

**Specification Data:**

81349-mil-m-38510/301 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0