

View Online at <https://aerobasegroup.com/nsn/5962-01-051-4853>

**Body Length:**

Between 0.371 inches and 0.400 inches

**Body Width:**

Between 0.247 inches and 0.285 inches

**Body Height:**

Between 0.050 inches and 0.080 inches

**Maximum Power Dissipation Rating:**

275.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Countermeasures set type an/alq-99 (v)

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and 3-state output and w/enable

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

8 input

**Design Function And Quantity:**

6 driver, bus

**Case Outline Source And Designator:**

-0-004-ag joint electron device engineering council

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

5.5 volts power source

**Time Rating Per Characteristic:**

21.00 nanoseconds propagation delay time, low to high level output and 27.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

03640-6088916 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

16 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0