## NSN 5962-01-052-3829

Linear Microcircuit - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5962-01-052-3829  |
|--|
| Body Length:   |
| Between 0.660 inches and 0.785 inches  |
| Body Width:  |
| Between 0.220 inches and 0.280 inches  |
| Body Height:   |
| Between 0.140 inches and 0.180 inches  |
| Maximum Power Dissipation Rating:  |
| 500.0 milliwatts   |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| End Application:   |
| Terminal, telephone type an/tcc-72   |
| Features Provided:   |
| Hermetically sealed and monolithic and negative outputs and positive outputs and externally compensated                                |
| Inclosure Material:  |
| Ceramic and glass  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Input Circuit Pattern:   |
| 4 input  |
| Design Function And Quantity:  |
| 1 amplifier, dc and 1 amplifier, wideband  |
| Case Outline Source And Designator:  |
| T0-116 joint electron device engineering council   |
| Terminal Surface Treatment:  |
| Gold or tin  |
| Precious Material And Location:  |
| Terminals gold   |
| Precious Material:   |
| Gold   |
| Test Data Document:  |
| 80063-sm-b-525570 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)                      |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |

**Fiig:** A458a0