

View Online at <https://aerobasegroup.com/nsn/5962-01-052-9504>

**Body Length:**

Between 0.750 inches and 0.795 inches

**Body Width:**

Between 0.245 inches and 0.300 inches

**Body Height:**

Between 0.120 inches and 0.195 inches

**Maximum Power Dissipation Rating:**

625.0 milliwatts

**Operating Temperature Range:**

+0.0/+75.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Computer, digital type pdp11-10ac

**Features Provided:**

Hermetically sealed and bipolar and high speed and monolithic and positive outputs and programmable and programmed and w/buffered output and w/decoded output and w/disable and w/enable and w/storage and w/open collector

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

10 input

**Case Outline Source And Designator:**

-0-001-ag joint electron device engineering council

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

5.5 volts power source

**Time Rating Per Characteristic:**

30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output

**Memory Device Type:**

Rom

**Memory Capacity:**

Unknown

**Test Data Document:**

15476-23a05a2 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0