NSN 5962-01-053-6306



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-053-6306 **Body Length:** Between 0.670 inches and 0.730 inches **Body Width:** Between 0.220 inches and 0.280 inches **Body Height:** Between 0.120 inches and 0.150 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Indicator, frequency type ip-1270/grr-3 (v) **Features Provided:** Monolithic and hermetically sealed and negative outputs and positive outputs and w/field effect transistor switch **Inclosure Material:** Glass and metal **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 2 channel **Design Function And Quantity:** 1 switch, analog **Terminal Surface Treatment:** Gold **Time Rating Per Chacteristic:** 1500.00 nanoseconds propagation delay time, low to high level output and 800.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminals gold and body gold **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Yes - demil/mli

Fiig:

A458a0