

View Online at <https://aerobasegroup.com/nsn/5962-01-054-3665>

**Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

**Body Height:**

Between 0.165 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

680.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Countermeasures set type an/tlq-17a

**Features Provided:**

Hermetically sealed and monolithic and high speed and positive outputs and high gain

**Inclosure Material:**

Glass and metal

**Inclosure Configuration:**

Can

**Input Circuit Pattern:**

2 input

**Design Function And Quantity:**

1 amplifier, video and 1 amplifier, wideband

**Case Outline Source And Designator:**

A-2 mil-m-38510

**Terminal Surface Treatment:**

Gold

**Time Rating Per Characteristic:**

25.00 nanoseconds propagation delay time, low to high level output and 25.00 nanoseconds propagation delay time, high to low level output

**Precious Material And Location:**

Terminals gold

**Precious Material:**

Gold

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0