NSN 5962-01-054-8019

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-054-8019

| View Offiline at https://derobasegroup.com/risin/0902-01-004-0015 |
|---|
| Body Outside Diameter: |
| Between 0.350 inches and 0.370 inches |
| Body Height: |
| Between 0.240 inches and 0.260 inches |
| Maximum Power Dissipation Rating: |
| 7.5 watts |
| Operating Tempurature Range: |
| -55.0/+150.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| Countermeasures set type an/tlq-17a |
| Features Provided: |
| Hermetically sealed and monolithic and negative outputs |
| Inclosure Material: |
| Glass and metal |
| Inclosure Configuration: |
| Can |
| Input Circuit Pattern: |
| 1 input |
| Design Function And Quantity: |
| 1 regulator, voltage |
| Case Outline Source And Designator: |
| T0-39 joint electron device engineering council |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| -35.0 volts power source |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig:

A458a0