NSN 5962-01-055-1872

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-055-1872

| Body Outside Diameter: | |
|---|------------------|
| Between 0.335 inches and 0.370 inches | |
| Body Height: | |
| Between 0.165 inches and 0.185 inches | |
| Maximum Power Dissipation Rating: | |
| 450.0 milliwatts | |
| Operating Tempurature Range: | |
| -55.0/+125.0 degrees celsius | |
| Storage Tempurature Range: | |
| -65.0/+150.0 degrees celsius | |
| Features Provided: | |
| Monolithic and hermetically sealed and negative outputs and positive outputs and w/field effect transistor switch and mediu | ım speed |
| Inclosure Material: | |
| Glass and metal | |
| Inclosure Configuration: | |
| Can | |
| Input Circuit Pattern: | |
| 2 channel | |
| Design Function And Quantity: | |
| 2 switch, analog | |
| Case Outline Source And Designator: | |
| T0-100 joint electron device engineering council | |
| Terminal Surface Treatment: | |
| Tin | |
| Time Rating Per Chacteristic: | |
| 500.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, | high to low leve |
| output | |
| Test Data Document: | |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| Yes - demil/mli | |
| Fiig: | |
| A458a0 | |