## NSN 5962-01-056-5265

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-056-5265 **Body Length:** 0.450 inches **Body Width:** Between 0.200 inches and 0.300 inches **Body Height:** Between 0.008 inches and 0.100 inches **Maximum Power Dissipation Rating:** 325.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Navigational set, loran, type an/arn-101 **Features Provided:** Hermetically sealed and monolithic and positive outputs and w/enable and presettable and w/clear and asynchronous and synchronous and high speed and resettable and edge triggered **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 9 input **Design Function And Quantity:** 1 counter, binary **Case Outline Source And Designator:** -0-004-ah joint electron device engineering council **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Test Data Document:** 35351-154826 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 flat leads Shelf Life:

**Demilitarization:** Yes - demil/mli

**Unit Of Measure:** 

N/a

## NSN 5962-01-056-5265

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0