

View Online at <https://aerobasegroup.com/nsn/5962-01-056-7020>

Body Length:

Between 0.240 inches and 0.275 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.030 inches and 0.070 inches

Maximum Power Dissipation Rating:

750.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Navigational set, loran, type an/arn-101

Features Provided:

Monolithic and hermetically sealed and negative outputs and w/enable and positive outputs and medium speed

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Input Circuit Pattern:

6 channel

Design Function And Quantity:

6 driver, switch, field effect transistor

Case Outline Source And Designator:

T0-86 joint electron device engineering council

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

6.0 volts power source

Time Rating Per Characteristic:

1500.00 nanoseconds propagation delay time, low to high level output and 500.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0