

View Online at <https://aerobasegroup.com/nsn/5962-01-056-7067>

Body Length:

Between 0.780 inches and 0.808 inches

Body Width:

Between 0.240 inches and 0.280 inches

Body Height:

Between 0.134 inches and 0.179 inches

Maximum Power Dissipation Rating:

625.0 milliwatts

Operating Temperature Range:

+0.0/+70.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and bipolar and monolithic and high speed and positive outputs and 3-state output and programmable and programmed and w/enable and w/buffered output and w/disable

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

6 input

Time Rating Per Characteristic:

50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

23259-es52spl-a2u13 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0