NSN 5962-01-057-0650

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-057-0650

Body Outside Diameter:
Between 0.597 inches and 0.603 inches
Body Height:
Between 0.150 inches and 0.175 inches
Maximum Power Dissipation Rating:
1.5 watts
Operating Tempurature Range:
55.0/+125.0 degrees celsius
Storage Tempurature Range:
65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and negative outputs and positive outputs and externally compensated
nclosure Material:
Glass and metal
nclosure Configuration:
Can
nput Circuit Pattern:
4 input
Design Function And Quantity:
1 amplifier, differential
Terminal Surface Treatment:
Gold
Time Rating Per Chacteristic:
20.00 nanoseconds propagation delay time, low to high level output and 25.00 nanoseconds propagation delay time, high to low level
putput
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Test Data Document:
97942-581r685 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Filg:
A458a0