NSN 5962-01-057-0651

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-057-0651

| Fiig: A458a0 | |
|------------------------|---|
| Yes - demil/mli | |
| Demilitarizatio | n: |
| Unit Of Measu | |
| N/a Unit Of Moasur | |
| Shelf Life: | |
| 16 printed circul | |
| | And Quantity: |
| | 383 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Test Data Docu | |
| output | |
| | econds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low lev |
| | er Chacteristic: |
| 17.0 volts powe | |
| | g And Type Per Characteristic: |
| Solder | a And Type Per Characteristics |
| Terminal Surfa | ace i reatment: |
| D-2 mil-m-3851 | |
| | Source And Designator: |
| 4 switch, analo | - |
| - | on And Quantity: |
| 4 channel | on And Quantity |
| Input Circuit Pa | |
| Dual-in-line | Jottorn. |
| Inclosure Conf | nguration: |
| Ceramic and gla | |
| Inclosure Mate | |
| | hermetically sealed and negative outputs and positive outputs and low power |
| Features Provi | |
| -65.0/+150.0 de | - |
| | urature Range: |
| -55.0/+125.0 de | - |
| | npurature Range: |
| 450.0 milliwatts | |
| Maximum Pow | ver Dissipation Rating: |
| Between 0.140 | inches and 0.185 inches |
| Body Height: | |
| Between 0.220 | inches and 0.310 inches |
| Body Width: | |
| 0.896 inches | |
| Body Length: | |