NSN 5962-01-057-0654

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-057-0654

Body Length:

Between 0.660 inches and 0.785 inches

Body Width:

Between 0.220 inches and 0.291 inches

Body Height:

0.200 inches

Maximum Power Dissipation Rating:

825.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Multiplexer-demultiplexer, type td-1147/tsc

Features Provided:

Hybrid and negative outputs and positive outputs and hermetically sealed and w/field effect transistor switch

Inclosure Material:

Ceramic and metal

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

2 channel

Design Function And Quantity:

1 switch, analog and 1 switch, field effect transistor

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.5 volts power source

Time Rating Per Chacteristic:

1500.00 nanoseconds propagation delay time, low to high level output and 600.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0