

View Online at <https://aerobasegroup.com/nsn/5962-01-057-1823>

Body Length:

Between 1.190 inches and 1.230 inches

Body Width:

Between 0.580 inches and 0.610 inches

Body Height:

Between 0.080 inches and 0.120 inches

Maximum Power Dissipation Rating:

804.4 milliwatts

Operating Temperature Range:

+0.0/+75.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and positive outputs and schottky and w/enable and w/decoded output and expandable and programmable and programmed and 3-state output and w/strobe and high speed and w/disable and w/buffered output and bipolar and w/storage

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

12 input

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Characteristic:

60.00 nanoseconds propagation delay time, low to high level output

Memory Device Type:

Rom

Memory Capacity:

Unknown

Precious Material And Location:

Terminals gold and lid gold

Precious Material:

Gold

Test Data Document:

23259-es52spl-a5u45 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0