

View Online at <https://aerobasegroup.com/nsn/5962-01-057-1823>

**Body Length:**

Between 1.190 inches and 1.230 inches

**Body Width:**

Between 0.580 inches and 0.610 inches

**Body Height:**

Between 0.080 inches and 0.120 inches

**Maximum Power Dissipation Rating:**

804.4 milliwatts

**Operating Temperature Range:**

+0.0/+75.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and schottky and w/enable and w/decoded output and expandable and programmable and programmed and 3-state output and w/strobe and high speed and w/disable and w/buffered output and bipolar and w/storage

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

12 input

**Terminal Surface Treatment:**

Gold

**Voltage Rating And Type Per Characteristic:**

5.5 volts power source

**Time Rating Per Characteristic:**

60.00 nanoseconds propagation delay time, low to high level output

**Memory Device Type:**

Rom

**Memory Capacity:**

Unknown

**Precious Material And Location:**

Terminals gold and lid gold

**Precious Material:**

Gold

**Test Data Document:**

23259-es52spl-a5u45 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

24 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0