## NSN 5962-01-057-7910

Digital Microcircuit - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5962-01-057-7910
Body Length:
Between 0.750 inches and 0.795 inches
Body Width:
Between 0.245 inches and 0.300 inches
Body Height:
Between 0.120 inches and 0.195 inches
Maximum Power Dissipation Rating:
160.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Memory loader model 6344
Features Provided:
Hermetically sealed and monolithic and positive outputs and medium power and medium speed and asynchronous and synchronous and
w/clear
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 5 input
Design Function And Quantity:
2 flip-flop, j-k, clocked
Case Outline Source And Designator:
-0-001-ag joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Test Data Document:
35351-154870 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a

Demilitarization: Yes - demil/mli

**Unit Of Measure:** 

## NSN 5962-01-057-7910

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0