NSN 5962-01-058-1046



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-058-1046 **Body Length:** 0.785 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 554.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Radar set, type an/fps-115 **Features Provided:** Hermetically sealed and monolithic and positive outputs and schottky and expandable and w/buffered output and high speed **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 9 input **Design Function And Quantity:** 1 generator, parity, checker **Case Outline Source And Designator:** D-1 mil-m-38510 **Terminal Surface Treatment:**

Solder

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Test Data Document:

49956-759720 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

NSN 5962-01-058-1046

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0