NSN 5962-01-058-1534

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-058-1534

| view Offilite at https://aerobasegroup.com/hsh/5302-01-030-1304 |
|--|
| Body Length: |
| Between 0.340 inches and 0.350 inches |
| Body Width: |
| Between 0.255 inches and 0.265 inches |
| Body Height: |
| Between 0.030 inches and 0.080 inches |
| Maximum Power Dissipation Rating: |
| 60.0 milliwatts |
| Operating Tempurature Range: |
| +0.0/+75.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+200.0 degrees celsius |
| End Application: |
| Radar set, type an/sps-52b |
| Features Provided: |
| Monolithic and hermetically sealed and positive outputs and medium speed |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Flat pack |
| Input Circuit Pattern: |
| Dual 4 input |
| Design Function And Quantity: |
| 2 driver, line |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 5.5 volts power source |
| Time Rating Per Chacteristic: |
| 40.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level |
| output |
| Test Data Document: |
| 05869-717315-6 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 14 flat leads |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Fiig:

A458a0

Yes - demil/mli