## NSN 5962-01-058-4417

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-058-4417

view Online at https://aerobasegroup.com/nsn/5962-01-056-4417
Body Length:
Between 0.755 inches and 0.785 inches
Body Width:
Between 0.245 inches and 0.280 inches
Body Height:
0.180 inches
Maximum Power Dissipation Rating:
60.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Data analysis central, type an/gyk-t1
Features Provided:
Hermetically sealed and monolithic and positive outputs and w/enable and 3-state output
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Hex 1 input
Design Function And Quantity:
6 driver, bus
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
16.00 nanoseconds propagation delay time, low to high level output and 22.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:

**Demilitarization:** Yes - demil/mli

## NSN 5962-01-058-4417

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0