## NSN 5962-01-058-5168

Linear Microcircuit - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5962-01-058-5168  |
|--|
| Body Length:   |
| Between 0.620 inches and 0.650 inches  |
| Body Width:  |
| Between 0.370 inches and 0.400 inches  |
| Body Height:   |
| 0.125 inches   |
| Maximum Power Dissipation Rating:  |
| 4.25 watts   |
| Operating Tempurature Range:   |
| -55.0/+85.0 degrees celsius  |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| End Application:   |
| Radar set type an/aps-125  |
| Features Provided:   |
| Hybrid and hermetically sealed and positive outputs and high speed   |
| Inclosure Material:  |
| Ceramic and glass  |
| Inclosure Configuration:   |
| Flat pack  |
| Input Circuit Pattern:   |
| Dual 2 input   |
| Design Function And Quantity:  |
| 2 driver, line   |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| 20.0 volts power source  |
| Time Rating Per Chacteristic:  |
| 15.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level       |
| output   |
| Test Data Document:  |
| 99971-7536971 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                              |
| Terminal Type And Quantity:  |
| 22 flat leads  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |

Fiig:

A458a0

Yes - demil/mli