## NSN 5962-01-058-6779

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-058-6779

view Online at https://aerobasegroup.com/hsh/5962-01-056-6779
Body Length:
Between 0.340 inches and 0.350 inches
Body Width:
Between 0.255 inches and 0.265 inches
Body Height:
Between 0.030 inches and 0.080 inches
Maximum Power Dissipation Rating:
44.0 milliwatts
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Storage Tempurature Range:
-65.0/+200.0 degrees celsius
End Application:
Radar set, @type an/sps-52b
Features Provided:
Hermetically sealed and monolithic and positive outputs and high speed
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Quad 2 input
Design Function And Quantity:
4 gate, nand-nor
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
10.00 nanoseconds propagation delay time, low to high level output and 10.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
05869-717315-47 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:

**Demilitarization:** Yes - demil/mli

## NSN 5962-01-058-6779

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0