

View Online at <https://aerobasegroup.com/nsn/5962-01-058-9434>

Body Length:

Between 0.371 inches and 0.390 inches

Body Width:

Between 0.250 inches and 0.285 inches

Body Height:

Between 0.060 inches and 0.080 inches

Maximum Power Dissipation Rating:

550.0 milliwatts

Operating Temperature Range:

-55.0/+110.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Radar set, type an aps-125

Features Provided:

Hermetically sealed and monolithic and positive outputs and w/enable and w/decoded output and synchronous

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

13 input

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Time Rating Per Characteristic:

20.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level output

Memory Device Type:

Ram

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Test Data Document:

99971-7537102 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0