NSN 5962-01-059-2587

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-059-2587 **Body Length:** Between 0.745 inches and 0.785 inches **Body Width:** Between 0.220 inches and 0.291 inches **Body Height:** Between 0.140 inches and 0.200 inches **Maximum Power Dissipation Rating:** 1000.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Radar set type an/aps-125 **Features Provided:** Hermetically sealed and monolithic and negative outputs and positive outputs and adjustable and externally compensated **Inclosure Material:** Ceramic and glass

graning arra grade

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

13 input

Design Function And Quantity:

1 converter, digital to analog

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Test Data Document:

99971-7540575 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0