NSN 5962-01-059-6992



Digital Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-059-6992 **Body Length:** 0.395 inches **Body Width:** 0.290 inches **Body Height:** 0.080 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+175.0 degrees celsius **End Application:** Radar set, type an/aps-125 **Features Provided:** Monolithic and hermetically sealed and negative outputs and w/enable **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 8 input **Design Function And Quantity:** 1 shift register **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -20.0 volts power source and 0.3 volts power source **Time Rating Per Chacteristic:** 80.00 nanoseconds propagation delay time, low to high level output and 80.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 99971-7537103 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 flat leads Shelf Life: N/a **Unit Of Measure:**

Fiig: A458a0

Demilitarization: Yes - demil/mli