## NSN 5962-01-061-4874

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-061-4874

View Online at https://aerobasegroup.com/nsn/5962-01-061-4874
Body Length:
Between 0.371 inches and 0.400 inches
Body Width:
Between 0.247 inches and 0.285 inches
Body Height:
Between 0.050 inches and 0.080 inches
Maximum Power Dissipation Rating:
320.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and w/open collector and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
7 input
Design Function And Quantity:
1 driver, decoder
Case Outline Source And Designator:
Mo-004ag joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
100.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 flat leads
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

## NSN 5962-01-061-4874

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0