NSN 5962-01-061-8852

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-061-8852

| view Offilite at https://defobasegroup.com/hsr//5502-01-0052 |
|---|
| Body Length: |
| Between 0.990 inches and 1.010 inches |
| Body Width: |
| Between 0.990 inches and 1.010 inches |
| Body Height: |
| Between 0.125 inches and 0.165 inches |
| Maximum Power Dissipation Rating: |
| 700.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+100.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and hybrid and positive outputs and adjustable |
| Inclosure Material: |
| Glass and metal |
| Inclosure Configuration: |
| Flat pack |
| Input Circuit Pattern: |
| 8 input |
| Design Function And Quantity: |
| 1 switch, analog |
| Terminal Surface Treatment: |
| Gold |
| Voltage Rating And Type Per Characteristic: |
| 22.0 volts power source |
| Precious Material And Location: |
| Body surface gold |
| Precious Material: |
| Gold |
| Test Data Document: |
| 88818-c574000295 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 16 flat leads |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Fiig:

A458a0

Yes - demil/mli