NSN 5962-01-061-8856

Linear Microcircuit - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5962-01-061-8856 |
|--|
| Body Length: |
| Between 0.990 inches and 1.010 inches |
| Body Width: |
| Between 0.990 inches and 1.010 inches |
| Body Height: |
| Between 0.130 inches and 0.150 inches |
| Maximum Power Dissipation Rating: |
| 1.3 watts |
| Operating Tempurature Range: |
| -55.0/+100.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and hybrid and positive outputs and negative outputs and externally compensated |
| Inclosure Material: |
| Glass and metal |
| Inclosure Configuration: |
| Flat pack |
| Input Circuit Pattern: |
| 9 input |
| Design Function And Quantity: |
| 1 multiplier, analog |
| Terminal Surface Treatment: |
| Gold |
| Voltage Rating And Type Per Characteristic: |
| -22.0 volts power source and 22.0 volts power source |
| Time Rating Per Chacteristic: |
| 460.00 nanoseconds propagation delay time, low to high level output and 500.00 nanoseconds propagation delay time, high to low level |
| output |
| Precious Material And Location: |
| Body surface gold |
| Precious Material: |
| Gold |
| Test Data Document: |
| 88818-c574000258 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 32 flat leads |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Yes - demil/mli

Demilitarization:

NSN 5962-01-061-8856

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0