## NSN 5962-01-062-0027

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-062-0027

| view Offilite at https://defobasegroup.com/hish/0302-01-002-002/  |
|---|
| Body Length:  |
| Between 0.990 inches and 1.010 inches   |
| Body Width:   |
| Between 0.990 inches and 1.010 inches   |
| Body Height:  |
| Between 0.130 inches and 0.150 inches   |
| Maximum Power Dissipation Rating:   |
| 920.0 milliwatts  |
| Operating Tempurature Range:  |
| -55.0/+100.0 degrees celsius  |
| Storage Tempurature Range:  |
| -65.0/+150.0 degrees celsius  |
| Features Provided:  |
| Hermetically sealed and hybrid and negative outputs and positive outputs and w/enable and adjustable                              |
| Inclosure Material:   |
| Glass and metal   |
| Inclosure Configuration:  |
| Flat pack   |
| Input Circuit Pattern:  |
| 11 input  |
| Design Function And Quantity:   |
| 1 loop, redundant   |
| Terminal Surface Treatment:   |
| Solder  |
| Voltage Rating And Type Per Characteristic:   |
| -15.0 volts power source and 15.0 volts power source  |
| Precious Material And Location:   |
| Body surface gold   |
| Precious Material:  |
| Gold  |
| Test Data Document:   |
| 88818-a574a319 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawin |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)                 |
| Terminal Type And Quantity:   |
| 32 flat leads   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| Yes - demil/mli   |

**Fiig:** A458a0