## NSN 5962-01-062-0028

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-062-0028 **Body Length:** Between 0.270 inches and 0.290 inches **Body Width:** Between 0.240 inches and 0.280 inches **Body Height:** Between 0.030 inches and 0.080 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and externally compensated and adjustable and negative outputs and positive outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 5 input **Design Function And Quantity:** 1 amplifier, differential and 1 amplifier, operational, general purpose **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -30.0 volts power source and 30.0 volts power source **Test Data Document:** 88818-a574a133 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 10 flat leads Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

Fiig:

A458a0