# NSN 5962-01-062-7560

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-062-7560

## **Body Length:**

Between 0.853 inches and 0.887 inches

## **Body Width:**

Between 0.481 inches and 0.515 inches

## **Body Height:**

Between 0.160 inches and 0.210 inches

# **Maximum Power Dissipation Rating:**

400.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **End Application:**

Test set, receiver-processor, type an/alm-174

#### **Features Provided:**

Monolithic and hermetically sealed and positive outputs and adjustable and bipolar

## Inclosure Material:

Glass and metal

#### Inclosure Configuration:

Dual-in-line

## Input Circuit Pattern:

4 input

#### **Design Function And Quantity:**

1 amplifier, reference

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

12.0 volts power source and 18.0 volts power source

#### Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Terminal Type And Quantity:

14 printed circuit

#### Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0