NSN 5962-01-062-8806

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-062-8806

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
350.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and negative outputs and positive outputs and internally compensated and high gain
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 amplifier, operational, general purpose
Case Outline Source And Designator:
A-2 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-20.0 volts power source and 20.0 volts power source
Time Rating Per Chacteristic:
800.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
10 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:
A458a0