NSN 5962-01-064-1325



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-064-1325 **Body Length:** Between 0.300 inches and 0.390 inches **Body Width:** Between 0.200 inches and 0.275 inches **Body Height:** Between 0.030 inches and 0.080 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and w/enable **Inclosure Material:** Glass and metal **Inclosure Configuration:** Flat pack **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 multiplexer **Terminal Surface Treatment:** Gold Voltage Rating And Type Per Characteristic: 16.3 volts power source **Time Rating Per Chacteristic:** 300.00 nanoseconds propagation delay time, low to high level output and 300.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal and body surfaces gold **Precious Material:** Gold **Terminal Type And Quantity:** 16 flat leads Shelf Life:

Demilitarization:

Unit Of Measure:

Yes - demil/mli

N/a

NSN 5962-01-064-1325

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0