## NSN 5962-01-064-1845

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-064-1845

View Online at https://aerobasegroup.com/nsn/5962-01-064-1845
Body Length:
Between 1.980 inches and 2.020 inches
Body Width:
Between 0.582 inches and 0.610 inches
Body Height:
0.100 inches
Maximum Power Dissipation Rating:
100.0 milliwatts
Operating Tempurature Range:
-25.0/+85.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and 3-state output and w/complement and w/enable and low power
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
12 input
Design Function And Quantity:
1 converter, analog to digital
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
12.0 volts power source
Time Rating Per Chacteristic:
500.00 nanoseconds propagation delay time, low to high level output and 500.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
40 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Fiig:

A458a0

**Demilitarization:** Yes - demil/mli