# NSN 5962-01-064-1845

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-064-1845

# **Body Length:**

Between 1.980 inches and 2.020 inches

# **Body Width:**

Between 0.582 inches and 0.610 inches

# **Body Height:**

0.100 inches

**Maximum Power Dissipation Rating:** 

100.0 milliwatts

#### **Operating Tempurature Range:**

-25.0/+85.0 degrees celsius

### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and 3-state output and w/complement and w/enable and low power

#### **Inclosure Material:**

Ceramic and glass

# Inclosure Configuration:

Dual-in-line

### **Output Logic Form:**

Complementary-metal oxide-semiconductor logic

### Input Circuit Pattern:

12 input

### **Design Function And Quantity:**

1 converter, analog to digital

## **Terminal Surface Treatment:**

Solder

### Voltage Rating And Type Per Characteristic:

12.0 volts power source

### Time Rating Per Chacteristic:

500.00 nanoseconds propagation delay time, low to high level output and 500.00 nanoseconds propagation delay time, high to low level output

### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

### Terminal Type And Quantity:

40 printed circuit

#### Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0