NSN 5962-01-064-9563

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-064-9563
Body Length:
Between 0.750 inches and 0.780 inches
Body Width:
Between 0.245 inches and 0.275 inches
Body Height:
Between 0.160 inches and 0.180 inches
Maximum Power Dissipation Rating:
660.0 milliwatts
Operating Tempurature Range:
-30.0/+85.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Strategic weapon systems (poseidon and trident).
Features Provided:
Hermetically sealed and monolithic and negative outputs and high speed and complementary outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Dual 3 input
Criticality Code Justification:
Feat
Design Function And Quantity:
2 comparator, voltage, differential
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.0 volts power source
Time Rating Per Chacteristic:
5.70 nanoseconds propagation delay time, low to high level output and 5.70 nanoseconds propagation delay time, high to low level output
Special Features:
Weapon system essential
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-01-064-9563

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0