# NSN 5962-01-065-8121

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-065-8121

## **Overall Length:**

0.414 inches

**Overall Height:** 

0.085 inches

## **Overall Width:**

1.000 inches

#### Body Length:

0.390 inches

#### **Body Width:**

Between 0.240 inches and 0.260 inches

### **Body Height:**

Between 0.030 inches and 0.085 inches

### **Maximum Power Dissipation Rating:**

22.0 milliwatts

### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

# Storage Tempurature Range:

-65.0/+150.0 degrees celsius

### Features Provided:

Hermetically sealed and monolithic and positive outputs and low power and schottky and w/totem pole output

#### **Inclosure Material:**

Ceramic and glass

### Inclosure Configuration:

Flat pack

### **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

Dual 4 input

### **Design Function And Quantity:**

2 gate, and

#### **Case Outline Source And Designator:**

F-2 mil-m-38510

### **Terminal Surface Treatment:**

Solder

### Voltage Rating And Type Per Characteristic:

5.5 volts power source

### **Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

14 flat leads

### **Specification Data:**

81349-mil-m-38510/310 government specification

# NSN 5962-01-065-8121

Digital Microcircuit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

