NSN 5962-01-065-9886

Digital Microcircuit - Page 1 of 1

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-065-9886 **Body Length:** Between 0.755 inches and 0.790 inches **Body Width:** Between 0.265 inches and 0.300 inches **Body Height:** Between 0.155 inches and 0.175 inches **Maximum Power Dissipation Rating:** 650.0 milliwatts Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Radar set type an/fps-115 **Features Provided:** Hermetically sealed and monolithic and positive outputs and w/storage and programmable and programmed and w/open collector and bipolar and w/enable and w/decoded output **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 10 input **Time Rating Per Chacteristic:** 30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 04761-640-200061 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli