NSN 5962-01-066-9602

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-066-9602

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
750.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-55.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and hybrid and high speed and negative outputs and positive outputs
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
4 input
Design Function And Quantity:
1 switch, analog and 1 switch, driver
Case Outline Source And Designator:
T0-100 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.0 volts power source
Time Rating Per Chacteristic:
30.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Terminal Type And Quantity:
10 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli

Fiig: A458a0