

View Online at <https://aerobasegroup.com/nsn/5962-01-067-1133>

Body Length:

1.005 inches

Body Width:

1.005 inches

Body Height:

0.280 inches

Maximum Power Dissipation Rating:

1.1 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Circuit card assembly p/n 566-504000-11 and p/n 566-504000-115

Features Provided:

Hybrid and hermetically sealed and multichip and resettable and positive outputs

Inclosure Material:

Glass and metal

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

2 channel

Design Function And Quantity:

1 driver, lamp, incandescent

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

34.0 volts power source

Time Rating Per Characteristic:

135000000.00 nanoseconds propagation delay time, low to high level output and 118000000.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Component body surfaces gold

Precious Material:

Gold

Test Data Document:

19133-4130001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

15 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0