

View Online at <https://aerobasegroup.com/nsn/5962-01-067-2818>

**Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

**Body Height:**

Between 0.165 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

350.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Indicator, panoramic type ip-1251/usq

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and negative outputs and high speed

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Can

**Input Circuit Pattern:**

4 input

**Case Outline Source And Designator:**

A-1 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

15.0 volts power source

**Time Rating Per Characteristic:**

44.00 nanoseconds propagation delay time, low to high level output

**Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 pin

**Specification Data:**

81349-mil-m-38510/106 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0